

# RDX<sup>®</sup> Media

*Rugged, Reliable, Removable*

The Tandberg Data RDX<sup>®</sup> technology is a disk-based removable media storage system which offers leading random access performance and high transfer rate like disk along with the archive life, removable/ portability and cost benefits of Tape. The RDX system consists of a drive and removable disk media with capacities fully forward and backward compatible. RDX is the best of disk and tape combined.

## High Reliability and Easy Handling

The Tandberg Data RDX media offers a rugged design for maximum data protection and secure handling. The media is well suited for data protection and archiving. It has an electrostatic proof design and is drop protected. New media types have to pass several tests before they are introduced to the market. This ensures high quality, reliability and durability. The media is keyed, so it is not possible to insert it into the drive in a wrong direction. A write protection switch prevents from deleting or overwriting data.

## HDD and SSD Versions

The RDX Media is offered in different versions to satisfy various business needs. The HDD-based media is suitable for most backup, archiving and storage tasks. It is available with capacities from 320GB up to 2TB and an affordable solution for SOHOs and smaller SMBs. The SSD-based version fulfils high performance requests and is ideal for data storage and data exchange of large files and for fast backups of big datasets. Its high transfer rate of 260MB/s ensures fast write and read operations. SSD media is ideal for very rough environments and withstands high temperature, humidity and vibration. SSD Media is available from 128GB to 512 GB.

## WORM for Compliance Archiving

RDX WORM media meets an expanded set of regulatory compliance requirements and is ideal for use with a large number of archiving applications, like enterprise content management and document management systems, where data must not be deleted or overwritten. WORM is a software based solution and is available for HDD media up to 1TB.

## Long Archival Life and Media Usage

RDX Media have an archival life of more than 10 years and insertion/ejection cycles of more than 5000 times. This enables RDX not only as an ideal media for backup and long term archiving but also for daily storage usage.



## Key Benefits

### == Rugged and Tough

Shock and drop protected design allows operation in rough environments and ensures durability. Vibration isolation ensures write/read performance reliability

### == High Quality

Designed for business grade applications to backup, archive and store business critical data

### == Static Protection

RDX Media are protected against electrostatic discharge events

### == Easy Handling

A keyed media is helping users to insert the cartridge correctly. The rugged design prevents damage from heavy handling

### == High Flexibility

HDD and SSD Versions fulfill performance requirements, various capacities for all business needs, WORM media for compliance archiving

### == No Compatibility Issues

New generation RDX Media works in all drives and older media works in new generation drives. Backward and Forward compatibility allows user to upgrade to higher capacity media without compromise

### == No Cleaning

No mechanical parts which require cleaning

### == High duty cycle

Over 5000 insertions/ejection, 10 years archival life

Positioning	HDD Media	SSD Media	WORM Media
Use Cases	Suitable for most storage applications	Premium media for high performance demands and harsh environments. Backup, restore of large datasets. Speed for use in work-flow or production environments.	Regulatory compliance storage device for document management applications, finance, video and voice recording, technical documentation
Backup	+	++	-
Archiving	+	-	++
Data Exchange	+	++	+/-
Advantages	Affordable High capacity	Fast data access High throughput	Meets regulatory requirements

Specifications	HDD Media	SSD Media	WORM Media
Capacity	320GB, 500GB, 1TB, 2TB	128GB, 256GB, 512GB	320GB, 500GB, 1TB
Performance			
Transfer Rate	USB 3.0: up to 120MB/s SATA: 45MB/s	<b>2x better:</b> USB 3.0: up to 260MB/s SATA: 45MB/s	USB 3.0: up to 120MB/s SATA: 45MB/s
Access Time	<15ms	<b>30x better:</b> < 0.5ms	<15ms
Compatibility	Compatible to all RDX drives		
Reliability and Data Integrity			
Unrecoverable Error Rate	1 error in 10 <sup>14</sup> bits read	<b>10x better:</b> 1 error in 10 <sup>15</sup> bits read	1 error in 10 <sup>14</sup> bits read
Drop Shock (non-operating)	1m drop to tile over concrete floor.	1.5m drop to tile over concrete floor.	1m drop to tile over concrete floor.
Load/Unload (minimum)	5000 insertion/removal cycles		
MTTF	550,000 Hours	<b>25x better:</b> 15,000,000 Hours	550,000 Hours
Environmental (operating)			
Temperature	10°C to 40°C (50°F to 104°F)		10°C to 40°C (50°F to 104°F)
Relative Humidity	20% - 80%, (non - condensing)		20% - 80%, (non - condensing)
Vibration	0.5G		0.5G
Altitude	-15m to 3,048m (-50ft to 10,000 ft)		-15m to 3,048m (-50ft to 10,000 ft)
Environmental (shipping)			
Temperature	-40°C to 65°C (-40°F to 149°F)	<b>20° larger temperature range:</b> -40°C to 85°C (-40°F to 185°F)	-40°C to 65°C (-40°F to 149°F)
Relative Humidity	8% - 90%, (non - condensing)	<b>8% more humidity tolerance:</b> 5% - 95%, (non - condensing)	8% - 90%, (non - condensing)
Maximum Wet Bulb	38°C (100°F), (non-condensing)	<b>Higher Wet Bulb temperature:</b> 40°C (104°F), (non-condensing)	38°C (100°F), (non-condensing)
Vibration	1G	<b>20x better:</b> 20G peak (Cartridge)	1G
Altitude	-15m to 10,660m (-50ft to 35,000 ft)	No limit	-15m to 10,660m (-50ft to 35,000 ft)
Archival Environmental			
Media Archive Life	<b>10x better:</b> 10 Years	Up to 1 year	<b>10x better:</b> 10 Years
Temperature	5°C to 26°C (41°F to 78°F)	Not specified	5°C to 26°C (41°F to 78°F)
Relative Humidity	8% - 90%, (non - condensing)	Not specified	8% - 90%, (non - condensing)
Maximum Wet Bulb	25°C (77°F), (non - condensing)	Not specified	25°C (77°F), (non - condensing)
Dimension (HxWxL)	23mm x 87mm x 119mm (0.9in x 3.4in x 4.7in)		
Weight	165g (0.364 lbs.) - 272g (0.600 lbs.) (HDD dependent)	130g (0.286lbs.)	165g (0.364 lbs.) - 272g (0.600 lbs.) (HDD dependent)

DS-RDX\_Media\_US\_2015

Overland Storage  
9112 Spectrum Center Blvd.  
San Diego, CA 92123  
USA  
Tel: (858) 571-5555  
Fax: (858) 571-3664  
sales@overlandstorage.com  
www.overlandstorage.com

Tandberg Data U.S.  
10225 Westmoor Dr., Ste. 125  
Westminster, CO 80021  
USA  
Tel: (800) 392-2983 Toll Free  
Fax: (303) 417-7170  
sales@tandbergdata.com  
www.tandbergdata.com/us

Tandberg Data EMEA  
Feldstrasse 81  
44141 Dortmund  
Germany  
Tel: 00 800 8263 2374 (00 800 TANDBERG)  
Fax: +49 (0) 231 5436 - 111  
salesemea@tandbergdata.com  
www.tandbergdata.com/emea

Tandberg Data APAC  
8 Cross Street, #28-00  
PWC Building  
Singapore 048424  
Tel: (65) 6850 7820  
Fax: (65) 6850 7889  
salesapac@tandbergdata.com  
www.tandbergdata.com/apac